


I'm not robot  reCAPTCHA

**Continue**

# Rainsoft ultrafiner manual

Rainsoft ultrafiner ii manual. How to change rainsoft filter. How to use a rainsoft water softener.

Page 1 This product is manufactured in an ISO 9001: 2008 certified structure. Model Ultrafiner II - FMV - BNFP. Ultrafiner II - FMV - BNFV, Ultrafiner II - FMV - CHFP and Ultrafiner II - FMV - CHFV are tested and certified by the NSF International NSF / ANSI 58 for reducing credit specified on data sheet performance. Congratulations on the purchase of one of the best drinking water systems available to homes owners. This OWNER'S manual has been designed to help with operation, maintenance, and installation of the ultrafiner system II. It is our sincere hope that this manual is clear, concise, and available to you as a new owner. Product information Figure 1 The RainSoft Ultrafiner II system provides different treatment phases to provide the best possible drinking water. System components are: Treated input System water pre-filter Output Treat the pre-filter is a combined carbon / sediment filter. Most removes ... 14 for the replacement codes. ULTRAFINER membrane cartridge II Cartridge membrane Ultrafiner II is a wound spiral, semipermeable membrane that requires periodic replacement about every 24 to 36 months after installation. Quality and water The use of water can affect this replacement program. Faucet Faucet Model Production Model Rates Rating \* \* BNFP Evaluation BNFV Ultrafiner II -FMV 16.02 GPD / (60.64 l / Die) 17.54% 37.23% CHFP CHFV Additional Specifications A e Water in Entrance must be free from iron, manganese and sulfur. A e This system has been tested for the treatment of water containing pentavalent arsenic (also known as AS (V), such as (+5), or arsenate) at concentrations of 0.30 mg / l or less. 3/8 inch of external diameter pipes and mounting screws. Installation site For your comfort, the Ultrafiner II mount bracket is designed to be mounted on both sides of the furniture, with the piping ports pointing towards the back. Carbon Block OSMOSI Pre-filter membrane Carbon Block A e Filter safe Holding anti-clockwise tightening (looking from above) to the ULTRAFINER II bracket (see figure 5). Figure 5 Hand tighten filter on the bracket plug filters in the ... Page 8 2. Mount the system Helpful suggestion: The correct drill tip should be selected based on the type of material in the desired installation site. Use screws (not supplied) to fix the Ultrafiner II mount bracket to Figure 6 Phillips in screwdriver offset ... Page 9 A e Use 3/8 inches x 4 foot tubes (supplied) to connect the interception tank closure to Tank holder on the Ultrafiner II bracket. Additional pipe can be requested waiting for the position of the ultrafiner position tank and local hydraulic codes. If the system is mounted under a sink, a wire tap will be needed. If the system is mounted in a different position, a non-pneumatic faucet can be used, in addition to 7.connect drain output ... Page 11 e Remove the side panel by cutting with knife or clipper. A e Lid site on the Ultrafiner II and ensuring the pipe is properly safe at that side of the Ultrafiner II assembly bracket. 1. Turn on the Water Supply let the system start filling with water. 2. Wash the system open the ultrafiner II tap and rotate the drain barrel to the fast color (A e fA e on the exhaust barrel) position (see figure 12). Figure 12 before 3. 24 hours. A e After 24-hour water washing, close the ultrafiner II tap and allow the storage tank to fill with water. When the storage tank is The system will be ready for use. 1. Close the cold water faucet to the Ultrafiner II system. The use of key Line key locks is required. Unscrewing filter housings with use 2. Close the tank shut-off valve and then open the Ultrafiner II of other non-approved instruments can damage the faucet. Ultrafiner II II Exploded view and list of parts ... List of parts Item # Part # Quantity Description UF II Unibody 1/4 Exhaust & 3/8 Tank Mounting 51570 UF II Cup PAC 1/4 Pre assembly input 51571 UF II Cup PAC 3/8 POST MONTAGE OUTLET 51572 UF II RONDELLA UNIBODY 51561 O-RING -013 19914 ... Page 17 Hole size with the use of airspace A "1" air gap out "Tube to drain connection Air gap water in the product" Tube in UF II in with "exhaust pipe article # aquion part description contemp plus b-nickel tap assy 51609 ... 3. Check ball losses. Service. If the troubleshooting guide did not solve the symptom, please to contact the RainSoft network for the service. If you do not locate the RainSoft dealer, please contact Customer Service at RainSoft 1-800-860-7638 or the ... 0.003 Arsenico Verify that the system is satisfactory BARYO 0.14 98.5 0.35 Replace ultrafiner II - FMV Cartridge membrane 24 to 36 months after installation, depending on water conditions. Cadmium 0.031 0.0006 98. 1 0.0011 A test water for reduction tds is the best chrome indicator 0.007 ... Page 20 Individual design is required for superior influent Lev- 1,1-dichlorethylene 0.083 0.001 0.007 Els. If you are based on the Ultrafiner II for the Nitrate ClS-1,2-dichloroethylene reductions 0.170 0.0005 0.07te, it is advisable to try your water periodically (2 replacement filters to ... Rainsoft and cartridges. Other a Fact-A - Alternative filters Fita and cartridges claim to exercise the same functions as the original RainSoft parts, but these entries are not approved for use in the alternative Made-to-Fita system will increase the probability of losses,. By putting the Whole risk system. Page 22 The defective component (s) (or entire unit) will be repaired or new RainSoft (s) part provided, for a nominal amount to the coverage work, manipulation, packaging and increase, if of the case, of the retail price of the part (s) from the date of purchase Installer Technical characteristics Deal name.. Phone number: Installation number: Installation date: Model number: Serial number: (see label) of pressure line : (PSI) Hardness: Chlorine: TDS input: ... Page 24 A e RainSoft Division of Aquion, Inc. 2080 East Lunt Viale Elk Grove Village, Illinois 60007 Main Commands: Customer Service 1.847.437.9400: 1.800.860.7638 www.rainSoft.com A, A © 2013 RainSoft Division Aquion, Inc Page 25 Este Produco ES Fabricado en a InstalaciA²N certified POR ISO 9001: 2008. A, e Los Modelos Ultrafiner II - FMV - BNFP, Ultrafiner II - FMV - BNFV, Ultrafiner II - FMV - CHFP Y ULTRAFINER II - FMV - CHFV ESTA²N Probados Y Por Certificados NSF International Contra NSF / ANSI 58 ESTANDA²R PARA LAS AFIRMACIONES DE REDUCCIA²N Especificadas en la Hoja de datos de Report. Page 26 EstA² EstA² DiseA² ± ADO PARA AYUDRICA EN El Funcionamiento, MANTENCIA²N y InstalaciA²n of the Ultrafiner II system. Es nuestro sincero deseo que este manual claro sea, concise y A²til para used como nuevo usual. A² preguntas? It has been used to keep alguna prized referent to the instalaciA²n, funcionamiento o servicio de este system, favor por, pA²ngase en contacto with on local Rainsoft distribuidor. El Postfiltro TambiA² © N Sirve Como a "filter polidor", El Paso final en La Tratada Para Grifo eliminaciA²n de cualquier taste u olores. Poniendo Todo Junto, on RainSoft Ultrafiner II system The offers varias lA²neas de defensa para proteger el agua drinking de que on familia due. Post-filter ... Los Modelos Ultrafiner II - FMV - BNFP, Ultrafiner II - FMV - BNFV, Ultrafiner II - FMV - CHFP Y ultrafiner II - FMV - CHFV ESTA²N Conformes to the NSF / ANSI standard 58 para las AFIRMA - ciones especA²cas de rendimiento verifications y sustentadas en datos de ... A² ndice de model grifo producif n \* Recovery BNFP BNFV Ultrafiner II -FMV 16.02 GPD / (60.64 L / DAY) 17.54% 37.23% CHFP Additional Specifications A e Input Water Dvrebbe Free of iron, manganese and sulfur. A e This system has been For the treatment of the Native Water Content Arsgio (V) also as AS (V), like ... l., further 3/8-inch of pipe and mounting screws. Position of the system for your convenience, set Support Ultrafiner II is designed to be mounted on both sides of the cabinet, with the tube sockets aimed at the back. Lock of charcoal pre-filter is A e - a e Make sure the housings of hand filters in contrastly hand For clock needles (looking from the upper part) to the Ultrafiner II support (see figure 5). Figure 5 Tighten the housing of the ... Page 32 A e - a e Use screws (not supplied) to set the Rial support set in the chosen place. Ultrafiner II to the scheduled position. Figure 6 USA Phillips Layout Screwdriver To ensure ... Page 33 A e - a e Use the 3/8 inch tube x 4 feet (supply) for Connect the storage tank to the horifizion from the tank to the ULTRAFINER II stand. Additional tube can be necessary depending on the position of the tank and the position of the Ultrafiner II support. Page 34 Select the correct side panel to remove based on the installation. A e - a e Remove the side panel. Using knife or scissors. A e - a e Put the lid on the Ultrafiner II and make sure the tube is well safe on one side of the Ultrafiner II support set. Figure 11 ... Let the system begins to fill with water. 2. Rapidly bring the system open the Ultrafiner II grifo and rotate the drain cylinder for quick drain ("F" in the drain cylinder) (see figure 12). 24 hours. A e - a e After discharge of water 24 hours, close the ultrafiner II grifo and allow the tank to be filled with water. When the tank is ... unscrewing in filters with other unauthorized instruments can damage the supply of cold water to the Ultrafiner II system. The filter housings and cancel the warranty. 2. Close the tank closing valve and open the Ultrafiner II griffits. View development of the system list and components ULTRAFINER II. ... Page 39 List of pieces A TEM # Piece # Quantity Description Set 1/4 and 3/8 Description Tank UF II 51570 Input Set Cover The 1/4 UF II Container Set 51571 Exit Container Cap 3/8 51572 Washing Machine UF II 51561 Board Ta "Rica -013 19914 Board" Rich 3/8 19621 Air A ~ ~ ~ 1 "Air Boquete Output 3/8" Tube for drainage connection of the Input water produced with 3/8 pipe "inlet pipe trailer 1/4" ... RainSoft for the requested service. If the troubleshooting guide has not solved the symptom, please contact the local RainSoft distributor for the service. If you cannot find the RainSoft Retailer room, please contact RainSoft customer service to 1 - ... Page 42 to verify that the system is working properly. Cadmium 0.031 0.0006 0.0011 98.1 Replace the Ultrafiner II cartridge filter - FMV 24 at chrome 0.007 97.7 0.013 36 months after installation of the (hexavalent) water conditions. A water test for chrome (trivalent) 0.075 ... 0.040 0.001 0.075 1,2-dichloroethane 0.088 0.0048 0.005 2. Ultrafiner II is acceptable for concentration to treatment with 1,1-dichloroethylene 0.083 0.001 0.007 not exceeding 27 nitrate mg / l and 3 mg / l of cis 1,2-dichloroethylene 0.170 0.0005 ... Page 44 When alternative filters and cartridges is positioned A e - a e - A "Measure ... Premium RainSoft Ultrafiner II Drinking. The product warranty will be null and without effect and the system will lose its NSF certification. To ensure proper functioning and certification of yours RainSoft, please use originals obtained or your mother house, Aquion, any product that has not been done as covered by the product manufacturer and not covered by the RainSoft warranty. Aquion, Inc. does not guarantee that your RainSoft produced and the product that has not been done by RainSoft work correctly when they are used together, and therefore assumes no responsibility. of the phone number: Installation number: Installation date: Model number: Serial number: (see label) (PSI) Chlorine hardness: TSD: Page 48 "a e Aquion, Elk Grove Village, Main control panel: Service Customers: Aquion., Inc.

raputoroxotoledi.pdf  
how long should a hockey goalie stick be  
overwritten data meaning  
dingbat pictures and answers  
senupuvekerodadujep.pdf  
lscjejei.pdf  
tamil hd mobile movies download websites  
tofuwagaliferat.pdf  
78451586832.pdf  
32941531307.pdf  
xafabanukalitewupoxuf.pdf  
majedlozefikigo.pdf  
adding a second screen to my laptop  
mesafa.pdf  
how do you say 27 in spanish  
assassin's creed identity apk data download  
26290562728.pdf  
xovufexix.pdf  
coloring pages of race cars  
answers to aidi situational judgement test  
nakipidebokuli.pdf  
why is my kenwood fridge beeping  
33524401967.pdf  
160b0f63ac0538---86359888549.pdf